



H1

SERIES

SINGLE PHASE



H1-3K-S2 | H1-3.6K-S2 | H1-4K-S2
H1-4.6K-S2 | H1-5K-S2 | H1-6K-S2

UPS With UPS function
switch time $\leq 10\text{ms}$



Fanless design
quiet and comfortable



Zero export function
supported

100A Max. 100A
charge current



24H energy monitoring
and management



Easy setting of
smart working modes

H1-3K/3.6K/4K/4.6K/5K/6K-S2

MODEL	H1-3K-S2	H1-3.6K-S2	H1-4K-S2	H1-4.6K-S2	H1-5K-S2	H1-6K-S2
DC Input						
Max. PV Array Power [Wp] @STC	4500	5400	6000	6900	7500	9000
Max. DC Voltage [V]	600					
MPPT Voltage Range [V]	90-550					
Rated DC Voltage [V]	360					
Start Voltage [V]	120					
Min. DC Voltage [V]	80					
Max. DC Input Current [A]	12.5/12.5					
Max. DC Short Circuit Current [A]	15/15					
No. of MPPT	2					
DC Switch	Integrated					
Battery Parameters						
Battery Type	Lithium battery					
Rated Input Voltage/Voltage Range [V]	48/42~58.5					
Rated Charging/ Discharging Current [A]	60/60			100/100		
Charging Mode Control	3-stages					
AC Output [On-grid]						
Rated AC Power [W]	3000	3680	4000	4600	5000 ^{*1}	6000
Max. Apparent Power [VA]	3000	3680	4000	4600	5000	6000
Rated AC Current [A]@230Vac	13.1	16.0	17.4	20.0	21.8 ^{*2}	26.1
Max. AC Current [A]	13.6	16.7	18.2	20.9	22.7	27.3
Rated Grid Voltage/Range [V]	220, 230, 240/180~280					
Rated Output Frequency [Hz]	50/ 60 ±5					
Power Factor [cos φ]	0.8 leading~0.8 lagging					
Total Harmonic Distortion [THDi]	< 3%					
Feed-in	L+N+PE					
AC Output [Back-up Mode]						
Rated Output Power [VA]	3000			4600	5000	
Peak Output Apparent Power [VA]	3600, 10s			5500, 10s	6000, 10s	
Output Voltage [V]	220/230/240					
Rated Output Frequency [Hz]	50/ 60 ±5					
Output THDv (@ Liner Load)	<3%					
Efficiency						
Max. Efficiency	97.6%					
Euro Efficiency	97.0%					
Max. Battery Charging Efficiency	94.6%					
Protection						
AC Short Circuit Protection	Integrated					
Overload Protection	Integrated					
DC Overvoltage/Undervoltage Protection	Integrated					
AC Overvoltage/Undervoltage Protection	Integrated					
AC Overfrequency/Underfrequency	Integrated					
Peak-to-trough Period Setting	Integrated					
Interface						
PV Connection	MC4					
Battery Connection	Terminal block					
Display	LCD					
Communication	Wi-Fi/ Ethernet/4G (Optional)					
General Data						
Operating Temperature Range	-25°C to +60°C (45°C to 60°C with derating)					
Cooling Method	Natural convection					
Ambient Humidity	0-100% non-condensing					
Altitude	4000m (>3000m power derating)					
Noise [dBA]	< 29					
Ingress Protection	IP65					
Dimensions [H*W*D] [mm]	470*470*190					
Weight [kg]	23					
Warranty [Year]	5/10/15/20					
Applicable Standard	IEC62109-1/2, IEC61000-6-1/2/3/4, EN50438, EN50549, C10/C11, IEC62116, IEC61727, RD1699, UNE 206006, UNE 206007, CEI 0-21, AS4777.2, CQC NB/T 32004, VDE-AR-N 4105					

Remarks: *1 For AS/NZS 4777.2 Rated Output Power is 4999VA. *2 For AS/NZS 4777.2 Rated Output Current is 21.7A.