

Technical Data

Suntrio Plus 25K/33K/40K/50K/60K

Type	Suntrio Plus 25K	Suntrio Plus 33K	Suntrio Plus 40K	Suntrio Plus 50K	Suntrio Plus 60K
Input (DC)					
Max. DC Power [W]	30300	36300	48400	60500	72000
Max. DC Voltage [V]			1000		
MPPT Voltage Range [V]	180-900			280-900	
Nominal DC Voltage [V]			600		
Start Voltage[V]	200			300	
Min. DC Voltage[V]	180			250	
Max. DC Input Current PV1 / PV2 [A]	22/22/22		40/30/30		40/40/40
Number of MPPT			3		
Number of DC Connection Sets per MPPT	2/2/2		4/3/3		4/4/4
DC Switch	Integrated				
Output (AC)					
Rated AC Power [W](@230V,50Hz)	25000	30000	40000	50000	60000
Max. AC Power [W]	27500	33000	44000	55000	60000
Rated AC Current [A]	37.9	45.5	61.0	76.0	87.0
Max. AC Current [A]	42.0	50.0	65.0	80.0	90.0
Nominal AC voltage/ range	3/N/PE, 220/380V, 230/400V, 240/415V; 180V-280V/312V-485V				
Grid frequency / range	50Hz, 60Hz / 44Hz-55Hz, 54-65Hz				
Power factor,adjustable [cos φ]	0.8 leading~0.8 lagging				
Total Harmonic Distortion (THDi)	< 3% (at nominal power)				
Feed-in	3L+N+PE				
Efficiency					
Max. Efficiency	98.6%	98.8%	98.8%	98.8%	98.9%
Euro Efficiency (@ 600Vdc)	98.4%	98.5%	98.5%	98.5%	98.6%
MPPT Accuracy	>99.5%				
Protection					
Internal Over-voltage Protection	Integrated				
DC Insulation Monitoring	Integrated				
DCI Monitoring	Integrated				
GFCI Monitoring	Integrated				
Grid Monitoring	Integrated				
AC Short Circuit Current Protection	Integrated				
LVRT	Integrated				
Thermal Protection	Integrated				
AC Surge Protection	Integrated (II)				
String Current Monitoring	Integrated				
Anti-PID Module	Optional				
DC Surge Protection	Integrated (II)				
DC Fuse	Optional				
Anti-island protection monitoring	AFD				
Interface					
DC Connection	MC4/H4				
AC Connection	Terminal Block				
LCD & LED Display	3.5 inch Graphic LCD Display				
Display Language	English				
Communication port	2*RS485、1*RS232				
Communication	Wi-Fi/GPRS/Ethernet (Optional)				
General Data					
Topology	Transformerless				
Consumption at Night [W]	<0.6				
Consumption at Standby [W]	<10				
Operating Temperature Range	-25°C to +60°C (45°C to 60°C with derating)				
Cooling Method	Intelligent fan				
Ambient Humidity	0% to 100% Non-condensing				
Altitude	3000m (> 2000m power derating)				
Noise [dBA]	<35				
Ingress Protection	IP65 (Indoor & Outdoor Installation)				
Mounting	Rear Panel				
Dimensions (H*W*D) [mm]	700*530*260		800*550*280		
Weight [kg]	48		68		
Standard Warranty [Year]	5 (Standard) / 10 / 15 / 20 / 25 (Optional)				
Certificates	IEC62109-1/2, IEC61000-6-2/3, IEC61683,IEC60068-2,IEC62116, IEC61727,PEA/MEA,NRS 097-2-1, UTE-C-15-712-1,VDE0126-1-1/A1, VDE-AR-N 4105, AS4777.2,AS4777.3,C-TICK,CQC NB/T 32004, G83-2,G59-3,NBR 16149,NBR 16150,TF 3.2.1				